



## Cam Gear Installation Instructions

Fidanza Performance thanks you for purchasing our high performance products and choosing us as your number one company for your driveline components. Before installing your new cam gear, please read these instructions to see the proper steps on how to install your Fidanza cam gear and review the limited warranty information. Be sure to visit [Fidanza.com](http://Fidanza.com) for other great performance products.

**Note:** If your vehicle has a camshaft position sensor mounted to the back of the original cam gear, it must be removed and attached to the corresponding gear.

- All adjusting bolts must be tightened with lock washers after making any adjustments. Torque to a maximum of 40-45 inch lbs.
- Adjusting bolts have been made as long as possible to facilitate ease of adjustment, it is critical that you check for adequate clearance, if you have a clearance issue, carefully grind the bolts for clearance before starting your engine. If clearance is not checked before starting the engine severe engine damage may result.
- **Caution!** - when adjusting your camshaft timing, be sure to verify that you have adequate valve to valve and valve to piston clearance - severe engine damage will result from inadequate clearance.

## Don't forget about our Short Throw Shifters!

Fidanza short throw shifters are built with the same quality and precision as our flywheels. We offer a wide range of shifters, from Vintage European to Domestic and Imports.

For more information or to locate a dealer near you, visit our website at [Fidanza.com](http://Fidanza.com).

Fidanza Performance, 4285 Main Street Perry OH 44081  
(P)440-259-5656 (F) 440-259-5588

